


**NOTES :**

1. PROJECT LOCATED IN LAKE JORDAN WATERSHED.
2. LAKE AMBERLY IS APPROVED AS WATERSHED PROTECTION DEVICE FOR ALL OF MORRIS BRANCH. (SEE PUD DOC. FOR OPEN SPACE AND BUFFERS)
3. ALL DRAINWAY PIPES ARE RCP.
4. ALL EASEMENTS ARE 20' EASEMENTS UNLESS OTHERWISE SHOWN.
5. ALL STORM DRAIN PIPES ARE 15" UNLESS OTHERWISE SHOWN.
6. STORM DRAINAGE MAY CHANGE FOR FINAL DESIGN CONST. DRAWINGS
7. SIGHT TRIANGLE ARE LOCATED WITHIN THE RIGHT-OF-WAY AT ALL INTERSECTIONS UNLESS OTHERWISE SHOWN. SIGHT DISTANCE TRIANGLES AREAS OUTSIDE OF THE RIGHT-OF-WAY SHALL BE KEPT FREE OF OBSTRUCTION PER TOWN OF CARY STANDARD SPECIFICATIONS AND DETAILS

**LEGEND**

- — — — — SILT FENCE
- — — — — TEMPORARY DIVERSION DITCH
- SEDIMENT BASIN
- CATCH BASIN
- YARD INLET
- — — — — CONSTRUCTION ENTRANCE



SF-A

**STORM DRAINAGE AND EROSION CONTROL**

**Hugh J. Gilleece and Associates**  
 875 Walnut St. Suite 350 Cary, NC ph(919)469-1101 fax(919)460-7837

Revisions:  
 1ST PRELIMINARY SUBMITAL

(H) Scale: 1"=100 ft.	Designed by:	Sheet:
(V) Scale: 1"=5 ft.	Drawn by:	3
F:\4003\400310R2.PRD	Date:	12/18/1998

*Handwritten notes:*  
 1/2  
 1/4  
 Am 8/1