



- NOTES:
- 1) DECK DRAIN IN POOL AREAS TO BE NYLOPLAST STANDARD GRATE 8" x 8" RATED FOR PEDESTRIAN USE OR EQUIVALENT.
  - 2) CONTRACTOR TO COORDINATE HOT BOX ELECTRICAL WITH BUILDING ELECTRICAL.
  - 3) POOL DECK SHALL DRAIN VIA SHEET FLOW TO OPEN SWALES OR STORM SEWERS.
  - 4) PRIOR TO DISCHARGE INTO STORM SEWERS THE POOL WATER MUST BE DECHLORINATED.

**CHAS. H. SELLS, INC.**  
 Consulting Engineers, Surveyors & Photogrammetrists  
 15401 Westcoast Parkway  
 Cary, NC 27513  
 Tel: 919-678-0035  
 Fax: 919-678-0206  
 www.chasells.com

RELEASED FOR CONSTRUCTION

**AMBERLY AR  
 RECREATION CENTER  
 CARY, NORTH CAROLINA**

05-SIP-135  
 APPROVED  
 TOWN OF CARY

Approved by: DC Date: 12-19-05  
 Planning: TC Date: 1-25-06  
 Engineering: TC Date: 1-19-06

NO.	DATE	DESCRIPTION

PROJECT #: 05-4029 DATE: 1/10/05  
 DRAWN BY: CD CHECKED BY: ET  
 TITLE:  
**POOL AREA  
 LAYOUT PLAN**  
 SHEET  
**C4.1**

FILITE HOMES  
 801 Corporate Center Drive  
 Raleigh, NC 27607

© CHASSELLS - ALL RIGHTS ARE RESERVED. ANY POSSIBLE REPRODUCTION OR OTHER USE OF THIS DOCUMENT WITHOUT PERMISSION FROM CHAS. SELLS, INC. IS EXPRESSLY PROHIBITED.